

BTICINO > Low voltage energy distribution > Circuit breakers for protection > BTDIN miniature circuit breakers > Combinable earth leakage modules



G43XF125

Earth leakage module 4P - type F - $I_n = 125A$ - $I_{dn} = 30mA$ - $V_n = 400 Vac$

Technical features

Brand	BTicino
Standard reference	CEI EN 60947-20
Rated voltage	400Vac
Rated current	125A
Earth leakage rated current	0.03A
Earth leakage type	F
N° of modules	6
N° of poles	4P
Protection index	IP20
Height	83mm
Width	107.2mm
Depth	76mm
Max section	50/70mmq
Series	Btdin

Documentation

 [Technical Data Sheet](#)

 [Instruction Sheet](#)

 [Tripping curves](#)

Related products



FT84C100

BTDIN160 - 4P thermal-magnetic curve C - In= 100A - Icu= 16kA - Vn= 400 Vac - 6 modules



FX84C25

BTDIN500 - 4P thermal-magnetic curve C - In= 25A - Icu= 50kA - Vn= 400Vac - 6 modules



FT84D125

BTDIN160 - 4P thermal-magnetic curve D - In= 125A - Icu= 16kA - Vn= 400 Vac - 6 modules



FX84C63

BTDIN500 - 4P thermal-magnetic curve C - In= 63A - Icu= 50kA - Vn= 400Vac - 6 modules



FV84C80

BTDIN250 - 4P thermal-magnetic curve C - In= 80A - Icu= 25kA - Vn= 400Vac - 6 modules



FT84D100

BTDIN160 - 4P thermal-magnetic curve D - In= 100A - Icu= 16kA - Vn= 400 Vac - 6 modules



FX84C50

BTDIN500 - 4P thermal-magnetic curve C - In= 50A - Icu= 50kA - Vn= 400Vac - 6 modules



FV84C125

BTDIN250 - 4P thermal-magnetic curve C - In= 125A - Icu= 25kA - Vn= 400Vac - 6 modules



FT84C80

BTDIN160 - 4P thermal-magnetic curve C - In= 80A - Icu= 16kA - Vn= 400 Vac - 6 modules



FX84C40

BTDIN500 - 4P thermal-magnetic curve C - In= 40A - Icu= 50kA - Vn= 400Vac - 6 modules