






G43XF63

Earth leakage module 4P - type F - $I_n = 63A$ - $I_{dn} = 30mA$ - $V_n = 400 Vac$

Technical features

Brand	BTicino
Standard reference	CEI EN 60947-10
Rated voltage	400Vac
Rated current	63A
Earth leakage rated current	0.03A
Earth leakage type	F
N° of modules	3
N° of poles	4P
Protection index	IP20
Height	83mm
Width	53.4mm

Documentation

-  [Instruction Sheet](#)
-  [Technical Data Sheet](#)
-  [Tripping curves](#)

Depth 76mm

Max section 50/70mmq

Series Btdin

Related products



FV84D50

BTDIN250 - 4P thermal-magnetic curve D - In= 50A - Icu= 25kA - Vn= 400Vac - 6 modules



FV84C40

BTDIN250 - 4P thermal-magnetic curve C - In= 40A - Icu= 25kA - Vn= 400Vac - 4 modules



FV84D40

BTDIN250 - 4P thermal-magnetic curve D - In= 40A - Icu= 25kA - Vn= 400Vac - 6 modules



FV84C32

BTDIN250 - 4P thermal-magnetic curve C - In= 32A - Icu= 25kA - Vn= 400Vac - 4 modules



FV84D32

BTDIN250 - 4P thermal-magnetic curve D - In= 32A - Icu= 25kA - Vn= 400Vac - 6 modules



FV84C63

BTDIN250 - 4P thermal-magnetic curve C - In= 63A - Icu= 25kA - Vn= 400Vac - 4 modules



FV84D63

BTDIN250 - 4P thermal-magnetic curve D - In= 63A - Icu= 25kA - Vn= 400Vac - 6 modules



FV84C50

BTDIN250 - 4P thermal-magnetic curve C - In= 50A - Icu= 25kA - Vn= 400Vac - 4 modules