

BTICINO > Low voltage energy distribution > Control and command devices > Earth leakage relays with separate toroids



G701Q

Earth leakage relay with separate toroids for panels of distribution boards 72x72mm - $I_{dn}=0,03-30A$ - $t=0-5s$ - 1NO/NC output contact

Technical features

Documentation

Brand	BTicino
Standard reference	EN 60947-2 annessi B e M
Rated voltage	230-400Vac
Earth leakage rated current	0.03-30A
Earth leakage type	A-S
Protection index	IP20
Height	72mm
Width	72mm
Max section	2.5mm ²
Series	Btdin

 [Instruction Sheet](#)

Related products



G701T/35N

Toroid for earth leakage relay item G701/2
diametre 35mm -
Idn=0,03A - In=150A



G701T/80N

Toroid for earth leakage relay item G701/2
diametre 80 mm -
Idn=0,03A - In=300A



G701T/110N

Toroid for earth leakage relay item G701/2
diametre 110 mm -
Idn=0,1A - In=600A



G701T/140N

Toroid for earth leakage relay item G701/2
diametre 140 mm -
Idn=0,3A - In=1200A



G701T/210N

Toroid for earth leakage relay item G701/2
diametre 210 mm -
Idn=0,3A - In=1800A



G701T/300A

Toroid for earth leakage relay item G701/2
diametre 300 mm -
Idn=1A - In=2000A