




G741AS25

Earth leakage circuit breaker 4P - type A-S - In= 25A - I_{dn}= 100mA - V_n= 400 Vac - 4 modules

Technical features

Brand	BTicino
Standard reference	CEI EN 61008-1
Rated voltage	400Vac
Rated current	25A
Earth leakage rated current	0.1A
Earth leakage type	A-S
N° of modules	4
N° of poles	4P
Protection index	IP20
Height	83mm
Width	71.2mm

Documentation

-  [Instruction Sheet](#)
-  [DWG drawing](#)
-  [Technical Data Sheet](#)

Certifications



Depth 77.5mm

Max section 25/35mmq

Series Btdin

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Source page: <https://catalogue.bticino.com/BT1-G741AS25-EN>