












H4691

Flush mounted thermostat with backlit display. It can be used to control the temperature of an individual zone, irrespective of a central unit being installed as part of the system or not. It features a temperature probe and an input for the connection of a contact line (e.g. window contact). It can be used for the management of different types of systems, and the adjustment of the fan speed when fan coils are used. Possibility of automatic operation (summer/winter), with compatible systems. SCS bus connection – 2 modules

Technical features

N° of modules	2
Standard reference	EN 60669-2-1EN 50491-5-1EN 50428
Rated voltage	27Vdc
Rated current	30 mA
Series	Axolute

Documentation

-  [Scheda Tecnica](#)
-  [Scheda Tecnica](#)
-  [Software Manual](#)
-  [Installer Manual](#)
-  [User Manual](#)
-  [Technical guide](#)
-  [My Home guidelines](#)
-  [Technical guide](#)
-  [Brochure](#)

Related products




F430V10

Actuator with 2 x 0-10 Volt outputs for the control of 0-10 proportional valves - SCS bus connection...



F430/2

2 independent relay actuator – for single and double loads: 6 A resistive, 2 A motor valves and pump...




F430R8

Actuator with 8 independent relays for the control of on-off valves, motorised valves (open-close an...



F430/4

4 independent relay actuator - for single, double and combined loads: 4 A resistive, 1 A motor valve...



F430R3V10

Actuator with 3 independent relays and 2 x 0-10 Volts outputs for the control of fan coils with 2 an...