



## K4430


Switch with passive infrared ray movement sensor, suitable for all types of load including LED lamps - 2 wires – variable threshold twilight circuit with possibility of exclusion – timing circuit to delay switching off adjustable from 10 seconds to 10 minutes - it has a selector switch for operating type ON - AUTO - OFF. It is possible to choose between two types of configuration: 1) visible selector switch (install the selector switch supplied and use the cover item. ...17SL) 2) hidden selector switch (do not install the selector switch supplied and use the cover item ...17) - power supply 230 Va.c. - 2 modules

### Technical features

Brand	BTicino
Rated voltage	240Vac
Rated current	20mA - 1A
Rated power W	3-250W
N° of modules	2
Series	Living Now

### Documentation

 [Technical sheet](#)

 [Living Now english catalogue](#)

## Related products



### KW17

Covers for 2-module IR switches without selector switch. For items K4430 (version without selector s...



### KG17

Covers for 2-module IR switches without selector switch. For items K4430 (version without selector s...



### KM17

Covers for 2-module IR switches without selector switch. For items K4430 (version without selector s...



### KW17SL

Covers for IR switches item K4430 (version with selector switch) K4432 - 2 modules - white



### KG17SL

Covers for IR switches item K4430 (version with selector switch) K4432 - 2 modules - black



### KM17SL

Covers for IR switches item K4430 (version with selector switch) K4432 - 2 modules - sand