

BTICINO > Low voltage energy distribution > Circuit breakers for protection > MEGATIKER - moulded case circuit breakers > Installation accessories



M7025


Padlock block for MA/MH160, MS200 and MA/MH/ML/MS250-250E

Technical features

Brand	BTicino
Series	Megatiker

Documentation

 [Instruction Sheet](#)

 [Catalogue Megatiker](#)

We, Bticino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in Bticino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". Bticino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Related products



T7313A/100

MA250 thermal-magnetic 3P - In=100A - Icu=36kA - Ue= 690Vac - thermal setting 0.64-1 In magnetic tri...



T7313LA/160

ML250 thermal-magnetic 3P - In=160A - Icu=100kA - Ue= 690Vac - thermal setting 0.64-1 In magnetic tri...



T7313A160S

MA250E electronic 3P - In=160A - Icu=36kA - Ue= 690Vac - 4 current and time settings for overload an...



T7313LA250S

ML250E electronic 3P - In=250A - Icu=100kA - Ue= 690Vac - 4 current and time settings for overload a...



T7313HA/160E

MH250E electronic 3P - In=160A - Icu=70kA - Ue= 690Vac - 2 current settings for overload and short-c...



T7313HA250T

MH250E electronic 3P - In=250A - Icu=70kA - Ue= 690Vac - 6 current and time settings for overload an...



T7313A/250

MA250 thermal-magnetic 3P - In=250A - Icu=36kA - Ue= 690Vac - thermal setting 0.64-1 In magnetic tri...



T7313LA/40E

ML250E electronic 3P - In=40A - Icu=100kA - Ue= 690Vac - 2 current settings for overload and short-c...



T7313A40S

MA250E electronic 3P - In=40A - Icu=36kA - Ue= 690Vac - 4 current and time settings for overload and...



T7313MA

MS250 disconnecter 3P - In=250A - Ue= 690Vac