

BTICINO > Low voltage energy distribution > Circuit breakers for protection > MEGATIKER - moulded case circuit breakers > Installation accessories



## M7045


Padlock block for MA/MH/ML400-630E and MA/MH/ML630MT

### Technical features

Brand	BTicino
Series	Megatiker

### Documentation

 [Instruction Sheet](#)

 [Catalogue Megatiker](#)

We, Bticino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in Bticino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". Bticino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

## Related products



### T743F250

M4 630F - thermal-magnetic circuit breaker 3P - In=250A - Icu=36kA - Ue= 690Vac - setting: Ir= 0.8...



### T743L500

M4 630L - thermal-magnetic circuit breaker 3P - In=500A - Icu=100kA - Ue= 690Vac - setting: Ir= 0....



### T743F500

M4 630F - thermal-magnetic circuit breaker 3P - In=500A - Icu=36kA - Ue= 690Vac - setting: Ir= 0.8...



### T743N250EB

M4 630N - electronic circuit breaker (Li) 3P - In=250A - Icu=50kA - Ue= 690Vac - setting: Ir= 0.4-...



### T743H500MP

MP4 630H - moulded case circuit breaker 3P for motor operator protection - In= 500A - Icu= 70kA



### T743N400M

M4 630N - electronic circuit breaker (Lsi) 3P - In=400A - Icu=50kA - Ue= 690Vac - setting: Ir= 0.4...



### T743L320MT

M4 630L - electronic circuit breaker (Lsig) 3P - In=320A - Icu=100kA - Ue= 690Vac - setting: Ir= 0...



### T743N630MT

M4 630N - electronic circuit breaker (Lsig) 3P - In=630A - Icu=50kA - Ue= 690Vac - setting: Ir= 0....



### T743F320MPE

MP4 630F - electronic circuit breaker 3P for motor operator protection - In= 320A - Icu= 36kA



### T743L630

M4 630L - thermal-magnetic circuit breaker 3P - In=630A - Icu=100kA - Ue= 690Vac - setting: Ir= 0....