




## T7072/250


GS250 underneath earth leakage module for MA/MH/ML/MS250  
- In=250A, I<sub>dn</sub>=0,03-3A, t=0-3s

### Technical features

Brand	BTicino
Standard reference	CEI EN 60947-2-A1
Rated voltage	500Vac
Rated current	100-250A
Earth leakage rated current	0.03-3A
Earth leakage type	A-S
N° of poles	4P
Height	108mm
Width	140mm
Depth	105mm
Series	MEGATIKER

### Documentation

 [DWG drawing](#)

 [Instruction Sheet](#)

## Related products



### T7314HA/100E

MH250E electronic 4P -  
In=100A - Icu=70kA -  
Ue= 690Vac - 2 current  
settings for overload and  
short-c...



### T7314HA160T

MH250E electronic 4P -  
In=160A - Icu=70kA -  
Ue= 690Vac - 6 current  
and time settings for  
overload an...



### T7314A/160

MA250 thermal-  
magnetic 4P - In=160A -  
Icu=36kA - Ue= 690Vac  
- thermal setting 0.64-1  
In magnetic tri...



### T7314LA/250

ML250 thermal-magnetic  
4P - In=250A -  
Icu=100kA - Ue=  
690Vac - thermal setting  
0.64-1 In magnetic tr...



### T7314A250S

MA250E electronic 4P -  
In=250A - Icu=36kA -  
Ue= 690Vac - 4 current  
and time settings for  
overload an...



### T7314LA40S

ML250E electronic 4P -  
In=40A - Icu=100kA -  
Ue= 690Vac - 4 current  
and time settings for  
overload an...



### T7314HA/250E

MH250E electronic 4P -  
In=250A - Icu=70kA -  
Ue= 690Vac - 2 current  
settings for overload and  
short-c...



### T7314HA40T

MH250E electronic 4P -  
In=40A - Icu=70kA - Ue=  
690Vac - 6 current and  
time settings for  
overload and...



### T7314A/40E

MA250E electronic 4P -  
In=40A - Icu=36kA - Ue=  
690Vac - 2 current  
settings for overload and  
short-ci...



### T7314LA100T

ML250E electronic 4P -  
In=100A - Icu=100kA -  
Ue= 690Vac - 6 current  
and time settings for  
overload a...