




T7073/250


GF250 underneath earth fault module for
MA/MH/ML/MS250-250E - In=250A

Technical features

Brand	BTicino
Standard reference	CEI EN 60947-2-A1
Rated voltage	500Vac
Rated current	250A
N° of poles	4P
Height	108mm
Width	140mm
Depth	105mm
Series	MEGATIKER

Documentation

 [DWG drawing](#)

 [Instruction Sheet](#)

Related products



T7314HA/100E

MH250E electronic 4P -
In=100A - Icu=70kA -
Ue= 690Vac - 2 current
settings for overload and
short-c...



T7314HA/160T

MH250E electronic 4P -
In=160A - Icu=70kA -
Ue= 690Vac - 6 current
and time settings for
overload an...



T7314A/160

MA250 thermal-
magnetic 4P - In=160A -
Icu=36kA - Ue= 690Vac
- thermal setting 0.64-1
In magnetic tri...



T7314LA/250

ML250 thermal-magnetic
4P - In=250A -
Icu=100kA - Ue=
690Vac - thermal setting
0.64-1 In magnetic tr...



T7314A250S

MA250E electronic 4P -
In=250A - Icu=36kA -
Ue= 690Vac - 4 current
and time settings for
overload an...



T7314LA/40S

ML250E electronic 4P -
In=40A - Icu=100kA -
Ue= 690Vac - 4 current
and time settings for
overload an...



T7314HA/250E

MH250E electronic 4P -
In=250A - Icu=70kA -
Ue= 690Vac - 2 current
settings for overload and
short-c...



T7314HA/40T

MH250E electronic 4P -
In=40A - Icu=70kA - Ue=
690Vac - 6 current and
time settings for
overload and...



T7314A/40E

MA250E electronic 4P -
In=40A - Icu=36kA - Ue=
690Vac - 2 current
settings for overload and
short-ci...



T7314LA/100T

ML250E electronic 4P -
In=100A - Icu=100kA -
Ue= 690Vac - 6 current
and time settings for
overload a...