

BTICINO > Low voltage energy distribution > Circuit breakers for protection > MEGATIKER - moulded case circuit breakers > MA/MH/ML250 thermal magnetic






T7313LA/250

ML250 thermal-magnetic 3P - In=250A - Icu=100kA - Ue=690Vac - thermal setting 0.64-1 In magnetic tripping 3.5-10In

Technical features

Brand	BTicino
Standard reference	CEI EN 60947-2
Rated voltage	690Vac
Rated current	250A
Ultimate breaking capacity Icu	100kA
N° of poles	3P
Height	200mm
Width	105mm
Depth	105mm
Series	Megatiker

Documentation

-  [Instruction Sheet](#)
-  [DWG drawing](#)
-  [Catalogue Megatiker](#)

Certificazioni



We, Bticino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in Bticino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". Bticino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Related products



M7025

Padlock block for
MA/MH160, MS200 and
MA/MH/ML/MS250-250
E



M7295

Terminal shields to
install between the poles
for MA/MH/ML/MS160-M
630E and
MA/MH/ML630MT