

BTICINO > Low voltage energy distribution > MEGATIKER - moulded cas circuit breakers > MA/MH/ML250E electronic



T7314A160S

MA250E electronic 4P - In=160A - Icu=36kA - Ue= 690Vac - 4 current and time settings for overload and short-circuit

Technical features

| | |
|----------------------------|----------------|
| Height | 200mm |
| Width | 140mm |
| Depth | 105mm |
| Standard reference | CEI EN 60947-2 |
| N° of poles | 4P |
| Ultimate breaking capacity | 36kA |
| Icu | |
| Rated voltage | 690Vac |
| Rated current | 160A |
| Series | Megatiker |

Documentation

-  [Instructions Sheet](#)
-  [Instructions Sheet](#)
-  [Catalogue Megatiker](#)

Related products



T7071/250

GL250 underneath earth leakage module for MA/MH/ML/MS250 - In=250A, I_{dn}=0,03-3A, t=0-3s - signalizat...



T7072/250

GS250 underneath earth leakage module for MA/MH/ML/MS250 - In=250A, I_{dn}=0,03-3A, t=0-3s



T7073/250

GF250 underneath earth fault module for MA/MH/ML/MS250-250 E - In=250A



M7025

Padlock block for MA/MH160, MS200 and MA/MH/ML/MS250-250 E



M7295

Terminal shields to install between the poles for MA/MH/ML/MS160-M 630E and MA/MH/ML630MT