

BTICINO > Low voltage energy distribution > MEGATIKER - moulded cas circuit breakers > MA/MH/ML250E electronic






T7314A160T

MA250E electronic 4P - In=160A - Icu=36kA - Ue= 690Vac - 6 current and time settings for overload and short-circuit and earth fault

Technical features

Height	200mm
Width	140mm
Depth	105mm
Standard reference	CEI EN 60947-2
N° of poles	4P
Ultimate breaking capacity	36kA
Icu	
Rated voltage	690Vac
Rated current	160A
Series	Megatiker

Documentation

-  [Instructions Sheet](#)
-  [Instructions Sheet](#)
-  [Catalogue Megatiker](#)

Related products



T7071/250

GL250 underneath earth leakage module for MA/MH/ML/MS250 - In=250A, I_{dn}=0,03-3A, t=0-3s - signalizat...



T7072/250

GS250 underneath earth leakage module for MA/MH/ML/MS250 - In=250A, I_{dn}=0,03-3A, t=0-3s



T7073/250

GF250 underneath earth fault module for MA/MH/ML/MS250-250 E - In=250A



M7025

Padlock block for MA/MH160, MS200 and MA/MH/ML/MS250-250 E



M7295

Terminal shields to install between the poles for MA/MH/ML/MS160-M 630E and MA/MH/ML630MT