

> MA/MH/ML160-250 circuit breakers > MA/MH/ML250E electronic



## T7314A250S

MA250E electronic 4P - In=250A - Icu=36kA - Ue= 690Vac - 4 current and time settings for overload and short-circuit

### Technical features

### Documentation

Brand	BTicino
Standard reference	CEI EN 60947-2
Rated voltage	690Vac
Rated current	250A
Ultimate breaking capacity	36kA
Icu	
N° of poles	4P
Height	200mm
Width	140mm
Depth	105mm
Series	MEGATIKER

 [Instruction Sheet](#)

 [Instruction Sheet](#)

## Related products



**T7071/250**

GL250 underneath earth leakage module for MA/MH/ML/MS250 - In=250A, I<sub>dn</sub>=0,03-3A, t=0-3s - signalizat...



**T7072/250**

GS250 underneath earth leakage module for MA/MH/ML/MS250 - In=250A, I<sub>dn</sub>=0,03-3A, t=0-3s



**T7073/250**

GF250 underneath earth fault module for MA/MH/ML/MS250-250 E - In=250A



**M7025**

Padlock block for MA/MH160, MS200 and MA/MH/ML/MS250-250 E



**M7295**

Terminal shields to install between the poles for MA/MH/ML/MS160-M 630E and MA/MH/ML630MT