

BTICINO &gt; Low voltage energy distribution &gt; MEGATIKER - moulded case circuit breakers &gt; MA/MH/ML250E electronic



## T7314LA250S

ML250E electronic 4P - In=250A - Icu=100kA - Ue= 690Vac - 4 current and time settings for overload and short-circuit

### Technical features

Height	200mm
Width	140mm
Depth	105mm
Standard reference	CEI EN 60947-2
N° of poles	4P
Ultimate breaking capacity	100kA
Icu	
Rated voltage	690Vac
Rated current	250A
Series	Megatiker

### Documentation

-  [Instructions Sheet](#)
-  [Instructions Sheet](#)
-  [Catalogue Megatiker](#)

## Related products



### T7071/250

GL250 underneath earth leakage module for MA/MH/ML/MS250 - In=250A, I<sub>dn</sub>=0,03-3A, t=0-3s - signalizat...



### T7072/250

GS250 underneath earth leakage module for MA/MH/ML/MS250 - In=250A, I<sub>dn</sub>=0,03-3A, t=0-3s



### T7073/250

GF250 underneath earth fault module for MA/MH/ML/MS250-250 E - In=250A



### M7025

Padlock block for MA/MH160, MS200 and MA/MH/ML/MS250-250 E



### M7295

Terminal shields to install between the poles for MA/MH/ML/MS160-M 630E and MA/MH/ML630MT