

BTICINO > Low voltage energy distribution > MEGATIKER - moulded case circuit breakers > M4 630F/N/L electronic



T743N500MT

M4 630N - electronic circuit breaker (Lsig) 3P - $I_n=500A$ - $I_{cu}=50kA$ - $U_e=690Vac$ - setting: $I_r=0.4-1I_n$, $T_r=3-30s$ (overload) - $I_{sd}=1.5-10I_n$, $T_{sd}=0-0,3s$ (short-circuit) - $I_g=0.2-1I_r$, $T_g=0.1-1s$ (earth fault) - with measuring function

Technical features

| | |
|----------------------------|----------------|
| Height | 260mm |
| Width | 140mm |
| Depth | 105mm |
| Standard reference | CEI EN 60947-2 |
| N° of poles | 3P |
| Ultimate breaking capacity | 50kA |
| Icu | |
| Rated voltage | 690Vac |
| Rated current | 500A |
| Series | Megatiker |

Documentation

-  [Instructions Sheet](#)
-  [Instructions Sheet](#)
-  [Catalogue Megatiker](#)

Related products



M7045

Padlock block for
MA/MH/ML400-630E
and MA/MH/ML630MT



M7295

Terminal shields to
install between the poles
for MA/MH/ML/MS160-M
630E and
MA/MH/ML630MT