

BTICINO > Low voltage energy distribution > MEGATIKER - moulded case circuit breakers > M4 630F/N/L thermal magnetic






T744F500

M4 630F - thermal-magnetic circuit breaker 4P - In=500A - Icu=36kA - Ue= 690Vac - setting: Ir= 0.8-1In (overload) - I_{sd}= 5-10In (short-circuit)

Technical features

Height	260mm
Width	183mm
Depth	105mm
Standard reference	CEI EN 60947-2
N° of poles	4P
Ultimate breaking capacity	36kA
Icu	
Rated voltage	690Vac
Rated current	500A
Series	Megatiker

Documentation

-  [Instructions Sheet](#)
-  [DWG drawing](#)
-  [Catalogue Megatiker](#)

Related products



T7081/400

GL400 underneath earth leakage module for MA/MH/ML/MS400 - $I_n=400A$, $I_{dn}=0,03-3A$, $t=0-3s$ - signalizat...



T7082/400

GS400 underneath earth leakage module for MA/MH/ML/MS400 - $I_n=400A$, $I_{dn}=0,03-3A$, $t=0-3s$



M7045

Padlock block for MA/MH/ML400-630E and MA/MH/ML630MT



M7295

Terminal shields to install between the poles for MA/MH/ML/MS160-M 630E and MA/MH/ML630MT