




## T744F630

M4 630F - thermal-magnetic circuit breaker 4P -  $I_n=630A$  -  $I_{cu}=36kA$  -  $U_e=690Vac$  - setting:  $I_r=0.8-1I_n$  (overload) -  $I_{sd}=5-10I_n$  (short-circuit)


### Technical features

Brand	BTicino
Standard reference	CEI EN 60947-2
Rated voltage	690Vac
Rated current	630A
Ultimate breaking capacity	36kA
$I_{cu}$	
N° of poles	4P
Height	260mm
Width	183mm
Depth	105mm
Series	MEGATIKER

### Documentation

 [DWG drawing](#)

 [Instruction Sheet](#)

 [Instruction Sheet](#)

## Related products



**T7081/400**

GL400 underneath earth leakage module for MA/MH/ML/MS400 - In=400A, I<sub>dn</sub>=0,03-3A, t=0-3s - signalizat...



**T7082/400**

GS400 underneath earth leakage module for MA/MH/ML/MS400 - In=400A, I<sub>dn</sub>=0,03-3A, t=0-3s



**M7045**

Padlock block for MA/MH/ML400-630E and MA/MH/ML630MT



**M7295**

Terminal shields to install between the poles for MA/MH/ML/MS160-M 630E and MA/MH/ML630MT