







## T744L400MT

M4 630L - electronic circuit breaker (Lsig) 4P -  $I_n=400A$  -  $I_{cu}=100kA$  -  $U_e=690Vac$  - setting:  $I_r=0.4-1I_n$ ,  $T_r=3-30s$  (overload) -  $I_{sd}=1.5-10I_n$ ,  $T_{sd}=0-0,3s$  (short-circuit) -  $I_g=0.2-1I_r$ ,  $T_g=0.1-1s$  (earth fault) - with measuring function

### Technical features

|                            |                |
|----------------------------|----------------|
| Brand                      | BTicino        |
| Standard reference         | CEI EN 60947-2 |
| Rated voltage              | 690Vac         |
| Rated current              | 400A           |
| Ultimate breaking capacity | 100kA          |
| $I_{cu}$                   |                |
| N° of poles                | 4P             |
| Height                     | 260mm          |
| Width                      | 183mm          |
| Depth                      | 105mm          |
| Series                     | MEGATIKER      |

### Documentation

-  [Instruction Sheet](#)
-  [Technical Data Sheet](#)
-  [Instruction Sheet](#)
-  [Instruction Sheet](#)

## Related products



**T7081/400**

GL400 underneath earth leakage module for MA/MH/ML/MS400 - In=400A, I<sub>dn</sub>=0,03-3A, t=0-3s - signalizat...



**T7082/400**

GS400 underneath earth leakage module for MA/MH/ML/MS400 - In=400A, I<sub>dn</sub>=0,03-3A, t=0-3s



**M7045**

Padlock block for MA/MH/ML400-630E and MA/MH/ML630MT



**M7295**

Terminal shields to install between the poles for MA/MH/ML/MS160-M 630E and MA/MH/ML630MT