

BTICINO > Low voltage energy distribution > MEGATIKER - moulded case circuit breakers > M4 630F/N/L electronic






T744L500EB

M4 630L - electronic circuit breaker (Li) 4P - $I_n=500A$ -
 $I_{cu}=100kA$ - $U_e= 690Vac$ - setting: $I_r= 0.4-1I_n$ (overload) - $I_{sd}= 1.5-10I_n$ (short-circuit)

Technical features

Height	260mm
Width	183mm
Depth	105mm
Standard reference	CEI EN 60947-2
N° of poles	4P
Ultimate breaking capacity	100kA
I_{cu}	
Rated voltage	690Vac
Rated current	500A
Series	Megatiker

Documentation

-  [Instructions Sheet](#)
-  [Instructions Sheet](#)
-  [Catalogue Megatiker](#)

Related products



T7081/400

GL400 underneath earth leakage module for MA/MH/ML/MS400 - $I_n=400A$, $I_{dn}=0,03-3A$, $t=0-3s$ - signalizat...



T7082/400

GS400 underneath earth leakage module for MA/MH/ML/MS400 - $I_n=400A$, $I_{dn}=0,03-3A$, $t=0-3s$



M7045

Padlock block for MA/MH/ML400-630E and MA/MH/ML630MT



M7295

Terminal shields to install between the poles for MA/MH/ML/MS160-M630E and MA/MH/ML630MT