

BTICINO > Low voltage energy distribution > Circuit breakers for protection > MEGATIKER - moulded case circuit breakers > M4 630 electronic




T744N320MT


M4 630N - electronic circuit breaker (Lsig) 4P - $I_n=320A$ - $I_{cu}=50kA$ - $U_e=690Vac$ - setting: $I_r=0.4-1I_n$, $T_r=3-30s$ (overload) - $I_{sd}=1.5-10I_n$, $T_{sd}=0-0,3s$ (short-circuit) - $I_g=0.2-1I_r$, $T_g=0.1-1s$ (earth fault) - with measuring function


Technical features


Documentation

Brand	BTicino
Standard reference	CEI EN 60947-2
Rated voltage	690Vac
Rated current	320A
Ultimate breaking capacity	50kA
I_{cu}	
N° of poles	4P
Height	260mm
Width	183mm
Depth	105mm
Series	MEGATIKER

 [Instruction Sheet](#)

 [Technical Data Sheet](#)

 [Instruction Sheet](#)

 [Instruction Sheet](#)

Related products



T7081/400

GL400 underneath earth leakage module for MA/MH/ML/MS400 - In=400A, I_{dn}=0,03-3A, t=0-3s - signalizat...



T7082/400

GS400 underneath earth leakage module for MA/MH/ML/MS400 - In=400A, I_{dn}=0,03-3A, t=0-3s



M7045

Padlock block for MA/MH/ML400-630E and MA/MH/ML630MT



M7295

Terminal shields to install between the poles for MA/MH/ML/MS160-M 630E and MA/MH/ML630MT