



T744N400EB

M4 630N - electronic circuit breaker (Li) 4P - $I_n=400A$ - $I_{cu}=50kA$
- $U_e=690Vac$ - setting: $I_r=0.4-1I_n$ (overload) - $I_{sd}=1.5-10I_n$
(short-circuit)


Technical features

Documentation

| | |
|----------------------------|----------------|
| Brand | BTicino |
| Standard reference | CEI EN 60947-2 |
| Rated voltage | 690Vac |
| Rated current | 400A |
| Ultimate breaking capacity | 50kA |
| I_{cu} | |
| N° of poles | 4P |
| Height | 260mm |
| Width | 183mm |
| Depth | 105mm |
| Series | MEGATIKER |

 [Instruction Sheet](#)

 [Technical Data Sheet](#)

 [Instruction Sheet](#)

 [Instruction Sheet](#)

Related products



T7081/400

GL400 underneath earth leakage module for MA/MH/ML/MS400 - In=400A, I_{dn}=0,03-3A, t=0-3s - signalizat...



T7082/400

GS400 underneath earth leakage module for MA/MH/ML/MS400 - In=400A, I_{dn}=0,03-3A, t=0-3s



M7045

Padlock block for MA/MH/ML400-630E and MA/MH/ML630MT



M7295

Terminal shields to install between the poles for MA/MH/ML/MS160-M 630E and MA/MH/ML630MT