

BTICINO > Low voltage energy distribution > Circuit breakers for protection > MEGATIKER - moulded case circuit breakers > M5 1600N/L electronic






T754N630M

M5 1600N - electronic circuit breaker (Lsi) 4P - $I_n=630A$ - $I_{cu}=50kA$ - $U_e= 690Vac$ - setting: $I_r= 0.4-1I_n$, $T_r= 3-30s$ (overload) - $I_{sd}= 1.5-10I_n$, $T_{sd}= 0-0,5s$ (short-circuit) - with measuring function

Technical features

Brand	BTicino
Standard reference	CEI EN 60947-2
Rated voltage	690Vac
Rated current	630A
Ultimate breaking capacity I_{cu}	50kA
N° of poles	4P
Height	320mm
Width	280mm
Depth	140mm
Series	Megatiker

Documentation

-  [Instruction Sheet](#)
-  [Instruction Sheet](#)
-  [Catalogue Megatiker](#)

We, Bticino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in Bticino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". Bticino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Related products



M7055

Padlock block for
MA/MH630-1600ES
electronics