

BTICINO > Low voltage energy distribution > MEGABREAK - Air circuit breakers > Draw-out circuit breakers Icu=42kA








T803BE 1600

Draw-out version air circuit breaker 3P - In= 1600A - Ue= 690Vac
- Icu= 42kA - Frame 1

Technical features

| | |
|----------------------------|----------------|
| Height | 465mm |
| Width | 316mm |
| Depth | 401mm |
| Standard reference | CEI EN 60947-2 |
| N° of poles | 3P |
| Ultimate breaking capacity | 42kA |
| Icu | |
| Rated voltage | 690Vac |
| Rated current | 1600A |
| Series | Megabreak |

Documentation

-  [Instructions Sheet](#)
-  [Instructions Sheet](#)
-  [Instructions Sheet](#)
-  [DWG drawing](#)
-  [Catalogue Megabreak](#)

Related products



MP4/BA

Standard electronic control unit with protection LI (overload and shortcircuit)



MP4/SA

Standard electronic control unit with protection LSI (overload and shortcircuit)



MP4/TA

Standard electronic control unit with protection LSGI (overload, shortcircuit and earth fault)



MP6SH

Touch screen electronic control unit with protection LSI (overload and shortcircuit)



MP6TH

Touch screen electronic control unit with protection LSGI (overload, shortcircuit and earth fault)