

BTICINO > Solution for energy efficiency > KNX Automation System > Modular controller



002654

Universal 2 channel KNX dimmer with maximum load 1.7 A when used separately, and 3.4A when used in parallel for the control of light loads. When associating up to three expansions, item 002660, it is possible to control up to 6 circuits. Main functions: ON/OFF switching - Manual or automatic dimmer using brightness sensors - Scenario control - Dimmer speed configuration - Minimum/maximum dimmer level setting Bus connection using a red-black KNX connector. Supply voltage 110 - 240 V 50-60 Hz. Fitting on DIN rail. Size: 4 DIN modules.

Technical features

Documentation

Brand	Legrand
Standard reference	EN 50090 - EN 13321-1 e ISO/IEC 14543-3
Rated voltage	29 Vdc
Rated current	3 mA
N° of modules	4 DIN
Protection index	IP 20 e IK 04
Cabling	KNX Bus
Plant type	KNX

 [DWG drawing](#)

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.