


BTICINO > Solution for energy efficiency > KNX Automation System > Gateway and interfaces



002692


Contact interface KNX 4 input channels and 4 output. Usable for interfacciamento traditional electromechanical controls to the KNX bus and display of status returns through display elements (LED). Main functions: - Switching or dimming - Control of sunscreens - Sending temperature values, levels ... - Sending multiple orders - Save / recall of scenarios - Sequential counter or differential Connection to the KNX bus via red-black KNX connector. Supply voltage SELV 29 V d.c from KNX bus. Installation in recessed box, size: 46x46x11.7mm

Technical features

Documentation

| | |
|--------------------|--|
| Brand | Legrand |
| Standard reference | EN 50090 - EN 13321-1 e ISO/IEC 14543-3 |
| Rated voltage | 29 Vdc |
| Rated current | 12 mA |
| Diameter | 46x46x11.7 mm |
| Cabling | KNX Bus |
| Plant type | KNX |

 [ETS Project File](#)

 [DWG drawing](#)

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.