

BTICINO &gt; Solution for energy efficiency &gt; KNX Automation System &gt; Sensors



## 048918


Ceiling mounted double technology KNX sensor, passive infrared and ultrasound (PIR+US), protection degree IP20. Ideal for installation in working areas (e.g. offices, conference and meeting rooms...). Bus connection using a red-black KNX connector. SELV 29 Vdc supply voltage from KNX bus. Flush mounted false ceiling or masonry ceiling installation using flush mounting boxes or springs; ceiling mounted installation using accessory item 048875. White colour

### Technical features

Brand	Legrand
Standard reference	EN 50090 - EN 13321-1 e ISO/IEC 14543-3
Rated voltage	29 Vdc
Rated current	7 mA (PIR) - 16 mA (PIR + US )
Protection index	IP 20 e IK 04
Diameter	Esterno 122 mm - incasso 52 mm
Cabling	KNX Bus
Plant type	KNX

### Documentation

 [\\_DWG drawing\\_](#)

 [ETS Project File](#)

## Related products



**088240**

Allows you to adjust the time delay, the brightness threshold and the detection sensitivity  
Possibi...



**048875**

Box for surface ceiling installation , compatible sensors : BMSA2202 , BMSA2204 , BMSA2205 , BMSE300...