

&gt; Motor protectors



## 417334

Motor protector 3P thermal-magnetic high breaking capacity with rotary handle -  $V_n=690V$  -  $I_r=18-26A$  -  $I_m= 338A$  -  $I_{cu}= 50kA$  (a 415Vac) - Pw motor 11W. Standard compliance IEC 60947-1, IEC 60947-2, IEC 60947-4. Thermic trip unit settable. Magnetic trip unit fixed ad 13Ie max

### Technical features

Brand	Legrand
Standard reference	CEI EN 60947-1/2/4
Rated voltage	690Vac
Rated current	18-26A
Ultimate breaking capacity	50kA
Icu	
N° of modules	2.5
N° of poles	3P
Protection index	IP20
Height	84mm
Width	46mm

Depth 76mm

Max section 6mmq

Series Btdin

## Related products



**417400**

Auxiliary contact 1NO+1NC for motor protector (max 2 contacts for motor protector). Mounting on the ...



**417406**

Alarm contact 1NO+1NC for motor protector. Report the trip of the motor protector in case of fault o...



**417411**

Shunt trip for motor protector  $V_n = 110\text{Vac} - 50\text{Hz} / 120\text{Vac} - 60\text{Hz}$ . Mounting on the right side of the ...



**417412**

Shunt trip for motor protector  $V_n = 220-230\text{Vac} - 50\text{Hz} / 240-260\text{Vac} - 60\text{Hz}$ . Mounting on the right side...



**417413**

Shunt trip for motor protector  $V_n = 380-400\text{Vac} - 50\text{Hz} / 440-460\text{Vac} - 60\text{Hz}$ . Mounting on the right side...



**417421**

Undervoltage release for motor protector  $V_n = 110\text{Vac} - 50\text{Hz} / 120\text{Vac} - 60\text{Hz}$ . Mounting on the right si...



**417422**

Undervoltage release for motor protector  $V_n = 220-230\text{Vac} - 50\text{Hz} / 240-260\text{Vac} - 60\text{Hz}$ . Mounting on the ...



**417423**

Undervoltage release for motor protector  $V_n = 380-400\text{Vac} - 50\text{Hz} / 440-460\text{Vac} - 60\text{Hz}$ . Mounting on the ...