

> Motor protectors



**417423**

Undervoltage release for motor protector  $V_n = 380-400\text{Vac} - 50\text{Hz} / 440-460\text{Vac} - 60\text{Hz}$ . Mounting on the right side of the motor protector (one release for motor protector). Senza contatti ausiliari

## Technical features

Brand	Legrand
Standard reference	CEI EN 23-105
Rated voltage	380-460Vac
N° of modules	1
Protection index	IP20
Height	84mm
Width	18mm
Depth	76mm
Max section	2.5mm <sup>2</sup>
Series	Btdin

## Related products



**417308**

Motor protector 3P thermal-magnetic with lever command - Vn=690V - Ir=4-6A - Im=78A - Icu= 100kA (a...



**417331**

Motor protector 3P thermal-magnetic high breaking capacity with rotary handle - Vn=690V - Ir=9-13A - ...



**417303**

Motor protector 3P thermal-magnetic with lever command - Vn=690V - Ir=0.4-0.63A - Im= 8.2A - Icu= 10...



**417312**

Motor protector 3P thermal-magnetic with lever command - Vn=690V - Ir=11-17A - Im= 221A - Icu= 20kA ...



**417335**

Motor protector 3P thermal-magnetic high breaking capacity with rotary handle - Vn=690V - Ir=22-32A ...



**417307**

Motor protector 3P thermal-magnetic with lever command - Vn=690V - Ir=2.5-4A - Im= 52A - Icu= 100kA ...



**417330**

Motor protector 3P thermal-magnetic high breaking capacity with rotary handle - Vn=690V - Ir=6-10A - ...



**417302**

Motor protector 3P thermal-magnetic with lever command - Vn=690V - Ir=0.25-0.4A - Im= 5.2A - Icu= 10...



**417311**

Motor protector 3P thermal-magnetic with lever command - Vn=690V - Ir=9-13A - Im= 169A - Icu= 50kA (...



**417334**

Motor protector 3P thermal-magnetic high breaking capacity with rotary handle - Vn=690V - Ir=18-26A ...