



BTICINO > ZUCCHINI busbar > MR Medium Rating > Aluminium Feed units

50401001


Right feed unit from cabinet to transformers for busbar in Al
MR160 - In=160A - IP55




Technical features


Protection index	IP55
Standard reference	CEI EN 61439-6
Rated voltage	1000V
Rated current	160A
Series	MR

Documentation

 [Instructions Sheet](#)


 [Busbar catalogue](#)

Related products




50400271-2400

Data Center straight elements (IP40). Aluminium conductors and windows on both sides (3+3, step 800m...




50400271-1600

Data Center straight elements (IP40). Aluminium conductors and windows on both sides (2+2, step 800m...




50400261

Data Center straight elements (IP40). Aluminium conductors and windows on both sides (5+5, step 600m...




50400261-2400

Data Center straight elements (IP40). Aluminium conductors and windows on both sides (4+4, step 600m...




50400261-1200

Data Center straight elements (IP40). Aluminium conductors and windows on both sides (2+2, step 600m...




50400101

Straight element MR160 AI with 3+3 outlets for side - In=160A - IP52 - length 3m



50400121

Straight element MR160 AI without outlets - In=160A - IP52 - length 1-1.5m




50400151

Straight element MR160 AI with 2+2 outlets for side - In=160A - IP52 - length 1.5-3m



50400111

Straight element MR160 AI without outlets - In=160A - IP52 - length 0.6-1m



50400141

Straight element MR160 AI with 1+1 outlets for side - In=160A - IP52 - length 1-1.5m