




BTICINO > ZUCCHINI busbar > LB PLUS DATA > Feed units



75221002D

Left feed unit + left end cover, for LB PLUS DATA - version 40A 8 conductors

Technical features

Protection index	IP55
Standard reference	CEI EN 61439-6
Rated voltage	400V
Rated current	40A
Series	Lbplus

Documentation

[Instructions Sheet](#)
[Instructions Sheet](#)
[Busbar catalogue](#)

Related products



75220102D

Straight element LB PLUS DATA 406 6 conductors In=40 A - IP55 - length 3 m - 4+4 outlets



75220111D

Straight element LB PLUS DATA 406 6 conductors In=40 A - IP55 - length 1,5 m - 1+1 outlets



75180102D

Straight element LB PLUS DATA 256 6 conductors In=25 A - IP55 - length 3 m - 4+4 outlets

We, Bticino S.p.A. Viale Borri 231-21100 Varese (Italy), declare that all items listed in Bticino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". Bticino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.